

Technical Bulletin

Concrete and Terrazzo Seal #510

Solvent Based Acrylic Seal

Quickly penetrates, providing a thorough, durable seal or finish coating. Resists oils, water vapor, alkali, and acids. Seals concrete preventing dusting. Avoids pitting and staining. Because it dries quickly, down time is kept to a minimum. should not be uses on linoleum, asphalt tile, vinyl asbestos tile, rubber or quarry tile.

Used with satisfaction by professionals and laymen alike. Excellent for factories, warehouses, garages, maintenance areas, parking lots, etc. High traffic areas can be easily recoated and maintained.

Areas of Use

- Maintenance Areas
- Warehouses
- Garages
- Factories
- Parking Lots, etc.

Physical Properties

| | |
|-----------------------|------------------|
| Form..... | Liquid |
| Odor..... | Aromatic Solvent |
| Color..... | Colorless |
| Sediment..... | None |
| Stability..... | 1 Year Min. |
| Cold Stability..... | Not Affected |
| Boiling Point..... | 230F |
| pH..... | N/A |
| Specific Gravity..... | 0.89 |
| Pounds/Gallon..... | 7.4 |
| Solids..... | 15.0 |
| Flash Point..... | 45F |

Packaging & Freight

| | |
|------------------|------|
| 55 Gallons..... | 445# |
| 35 Gallons..... | 287# |
| 20 Gallons..... | 162# |
| 6 Gallons..... | 46# |
| 5 Gallons..... | 37# |
| 4/1 Gallons..... | 32# |

Diversified Chemical Products
4124 Northeast Riverside Street
Riverside, Missouri 64150
United States of America
+1.816.472.5515 phone
www.diversifiedchemicalproducts.com



DCP
Diversified Chemical Products