

Technical Bulletin

Lift-X

#550

Emulsifiable Lift Station Degreaser

A degreaser manufactured for use specifically in lift stations.

An emulsifiable type degreaser. Does not contain any acids, and is alkali free. Non-freezing - used year round. Designed to clean lift stations, eliminate grease balls, and keep digesters from sticking.

Lift Stations: Turn on manual operation, pump completely down, add 20 gallons of degreaser for every 500 gallons in lift station, let rise to the maximum, turn back on automatic operation.

Digesters: Add 20 gallons of degreaser for each foot of scum and let sit for 20 minutes. Agitate or recirculate digester.

Trickling Filter: Simply apply with a sprayer.

Over All Plant: Drip into influent at the rate of 1/2 to 1 1/2 ppm.

Applications

- Lift Stations
- Digesters
- Trickling Filters

Areas of Use

- Industry
- Manufacturing Plants
- Machine Shops
- Printing Plants

Diversified Chemical Products
4124 Northeast Riverside Street
Riverside, Missouri 64150
United States of America
+1.816.472.5515 phone
www.diversifiedchemicalproducts.com

Physical Properties

Form.....	Liquid
Odor.....	Mild
Color.....	AmberBrown
Clarity.....	Clear
Sediment.....	None
Stability.....	1 Year Min.
Cold Stability.....	Not Affected
Boiling Point.....	280F
pH.....	N/A
Specific Gravity.....	0.86
Pounds/Gallon.....	7.2
Foaming.....	Low
Flash Point.....	120F

Packaging & Freight

55 Gallons.....	434#
35 Gallons.....	280#
20 Gallons.....	158#
6 Gallons.....	45#
5 Gallons.....	38#
4/1 Gallons.....	30#



DCP

Diversified Chemical Products