



QUIKLEEN II

SOLVENT CLEANER DEGREASER

DESCRIPTION

QUIKLEEN II is a USDA authorized non-flammable and non-conductive parts cleaner. Safe for use on metal parts, electric motors and electronic subassemblies. Quickly cleans oil, grease and dirt from parts without leaving residue. Displaces moisture from electric motors. Can be used while equipment is operating. Dielectric strength of 29,000 volts. Contains no 1,1,1 Trichloroethane. Product must be tested prior to using on any plastic.

APPLICATIONS

For electrical motors, ignition systems, electronic parts, and refrigeration equipment. Areas of use include machine shops, factories, industrial plants, offices, automotive and bus repair shops, printing industry, electrical maintenance services, marine sales and repair.

FEATURES & BENEFITS

- Fast drying
- Contains no oil, leaves no residue
- Non-flammable and non-conductive
- Non-ozone depleting

SPECIFICATIONS

FORM: Solvent Based Aerosol
ODOR: Chlorinated Solvent
COLOR: Clear
DETERGENCY: None
TOXICITY: 25 ppm OSHA PEL
WETTING ABILITY: Saturates
STORAGE STABILITY: 1 Year +
COLD STABILITY: 0°F
PHOSPHATES: None

FLASH POINT: None
FLAME EXTENSION: None
SOLUBILITY IN WATER: 0%
SPECIFIC GRAVITY: 1.52
% VOLATILE BY VOLUME: 100%
pH: N/A
PROPELLANT: Carbon Dioxide
EVAPORATION RATE: Fast
BIODEGRADABILITY: None

LABEL INFORMATION

QUIKLEEN II SOLVENT CLEANER

A highly concentrated solvent designed to remove dirt, grease, oil and grime from metallic and nonmetallic surfaces. Cleaning is quick and simple without the danger of injury to working parts. Ideally suited for use on electric motors even while running, electronic equipment, ignition systems, generators, power tools, and for air conditioning, refrigeration and all types of mechanical equipment.

NOTE: Do not use on automatic electronic process control or monitoring systems, computers or data processing equipment. May affect certain plastics. Test before using.

Authorized by USDA for use in federally inspected meat and poultry plants.


DIRECTIONS: Remove cap and spray generously over the surface to be cleaned until completely wet. Allow the solvent to set for a minute, then wipe or rinse off with a second spray. On heavily encrusted areas use a brush. Product is nonflammable and nonconductive so it can be used while motors and equipment are operating.

WARNING: Contains trichloroethylene and tetrachloroethylene. Use only in a well ventilated area. Avoid prolonged breathing of vapor. Avoid contact with eyes and prolonged contact with skin. In case of eye contact, flush thoroughly with water. If irritation persists, get medical attention. Keep out of the reach of children. Contents under pressure. Do not use or store near heat or open flame. Do not puncture or incinerate container. Exposure to temperatures above 120°F may cause bursting.

WARNING: This product contains chemical(s) known to the State of California to cause cancer.

CONTAINS (CAS#): Trichloroethylene (79-01-6), Carbon Dioxide (124-38-9), Tetrachloroethylene (127-18-4).

| | |
|--------------|---|
| HEALTH | 3 |
| FLAMMABILITY | 1 |
| REACTIVITY | 1 |
| PERSONAL | C |



PACKAGING INFORMATION

12 - 16 oz cans per case, 16 oz net weight