

SLIDE OUT

DRY SILICONE SPRAY—FOOD GRADE

DESCRIPTION

SLIDE OUT is designed to lubricate equipment used in the packaging and processing industry. Slide Out leaves a non-staining, dry, pure silicone film to lubricate moving parts, reducing friction and wear. **SLIDE OUT** is heat stable from -30°F to 300°F. Also formulated as a release agent on seals and gaskets of tank closures. Lubricates all sliding surfaces except those you wish to paint. Excellent on RV slide outs. Use on sticking metal, wood, rubber and plastic. Apply to cutting tables, conveyors, heat sealing equipment and slicing equipment. Waterproofs leather, canvas, rubber and chrome surfaces. Safe on all plastics. Contains no methylene chloride. Won't melt, freeze, gum or become rancid.

APPLICATIONS

An excellent product for food processing plants, restaurants, apparel and accessory manufacturing, tank closure seals, plastic products, RV dealers, hotels/motels, machine shops, homes, service hinges, RV slide outs, auto/RV repair shops and institutions.

FEATURES & BENEFITS

- Concentrated formula. A little **SLIDE OUT** goes a long way.
- Reduces friction between moving parts even for metal-to-metal contact surfaces. Parts last longer.
- Clean, dry spray does not leave a sticky residue behind.

SPECIFICATIONS

FORM: Solvent-Based Aerosol	FLASH POINT: <5°F TCC
ODOR: Mild Solvent	FLAME EXTENSION: None
COLOR: Clear	SOLUBILITY IN WATER: 40%
DETERGENCY: None	SPECIFIC GRAVITY: 0.76
TOXICITY: 400 ppm OSHA TLV	% VOLATILE BY VOLUME: 96%
WETTING ABILITY: Slight	pH: N/A
STORAGE STABILITY: 1 Year +	PROPELLANT: Hydrocarbon
COLD STABILITY: 0°F	EVAPORATION RATE: Fast
PHOSPHATES: None	BIODEGRADABILITY: None

LABEL INFORMATION

SLIDE OUT
DRY SILICONE SPRAY
FOOD GRADE

This Dry Silicone Spray Food Grade is designed to lubricate equipment used in the packaging and processing industry. Leaves a non-staining dry pure silicone film to lubricate moving parts, reducing friction and wear. Product is heat stable from -30°F to 300°F. Also formulated as a release agent on seals and gaskets of tank closures. Lubricates all sliding surfaces except those you wish to paint. Excellent on RV slide outs. Use on sticking metal, wood, rubber and plastic. Apply to cutting tables, conveyors, heat sealing equipment and slicing equipment. Waterproofs leather, canvas, rubber and chrome surfaces. Safe on all plastics. Contains no methylene chloride. Won't melt, freeze, gum or become rancid.


DIRECTIONS

Read cautions and directions carefully before use. Area to be lubricated should be clean and dry. Shake well before use. Hold can 6-8 inches from surface. Spray in short bursts. Spray no more than required to lubricate surface. Do not spray electrical equipment while in use. Wait 5-10 minutes before operating electrical equipment after using. Spray is dry. Do not expect a liquid. Used as directed, it will not harm most surfaces.

CAUTION: Contents under pressure. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F. Do not spray on hot surfaces. Accumulated vapor may be flammable. Contains petroleum distillate. Keep out of the reach of children.

CONTAINS (CAS#): Acetone (67-64-1), Propane/n-Butane (68476-86-8), Heptane (142-82-5), Polydimethylsiloxane (63148-62-9).

HEALTH	1
FLAMMABILITY	3
REACTIVITY	1
PERSONAL	A



PACKAGING INFORMATION

12 – 20 oz. cans per case, 11.5 oz. net weight