

PURITY

FOOD GRADE LUBRICANT & PROTECTANT



DESCRIPTION

PURITY is a lubricant made up of USP liquid petrolatum and propellant, providing a sanitary means of lubricating dairy and food processing equipment. Resists water washout and has an operating range of 0°F to 300°F. Complies with FDA regulations, CFR Title 21, paragraphs 172.878 and 173.3620.

APPLICATIONS

An excellent product for use on slides, bearings, pistons and rings, seals and pump parts, belts, etc. Great for use in fast service food preparation, cut meat cold room packaging in supermarkets, packaged meat units for franchise outlets, ice cream filling equipment, milk bottle equipment.

FEATURES & BENEFITS

- Non-Toxic
- Odorless & Tasteless
- Contains No Silicone

SPECIFICATIONS

FORM: Solvent Based Aerosol	FLASH POINT: <390°
ODOR: None	FLAME EXTENSION: 18"
COLOR: Clear	SOLUBILITY IN WATER: 45%
DETERGENCY: None	SPECIFIC GRAVITY: 0.85
TOXICITY: 400 ppm OSHA TLV	% VOC: 10%
WETTING ABILITY: Slight	VISCOSITY (SUS @ 100°F): 330-366
STORAGE STABILITY: 1 Year +	PROPELLANT: Hydrocarbon
COLD STABILITY: 0°F	EVAPORATION RATE: Slow
PHOSPHATES: N/A	BIODEGRADABILITY: Yes

LABEL INFORMATION

PURITY FOOD GRADE LUBRICANT & PROTECTANT

PURITY is a lubricant made up of USP liquid petrolatum and propellant, providing a sanitary means of lubricating dairy and food processing equipment. Resists water washout and has an operating range of 0°F to 300°F. Complies with FDA regulations, CFR Title 21, paragraphs 172.878 and 173.3620.

USED ON: Slides, bearings, pistons and rings, seals and pump parts, pans, containers, belts, etc.

USED IN: Fast Service Food Preparation, Cut Meat Cold Room Packaging in Supermarkets, Packaged Meat Units for Franchise Outlets, Ice Cream Filling Equipment, Milk Bottle Equipment.

DIRECTIONS:


Spray 8-10 inches from surface to be lubricated. Leaves a pure food grade oil film. Reapply periodically.

DANGER: Extremely Flammable Aerosol. Contains gas under pressure; may explode if heated.

Keep away from heat, sparks, open flames, and hot surfaces. –No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place.

CONTAINS (CAS#): White Mineral Oil (8042-47-5), Liquefied Petroleum Gas (64876-85-7).

HEALTH	1
FLAMMABILITY	3
REACTIVITY	0
PERSONAL	A



Nonfood Compounds
H1
148100

PACKAGING INFORMATION

12 – 20 oz. cans per case, 16 oz. net weight