



PIERCE PENETRATING LUBRICANT

DESCRIPTION

PIERCE is a USDA authorized lubricating product. Formulated to quickly penetrate rust, corrosion and moisture. Lubricates, cleans and contains rust preventative. Non-flammable and non-conductive to 30,000 volts. Four-way action cleans, lubricates, prevents rust and penetrates. Due to VOC regulations, not available for sale in California.

APPLICATIONS

For use on motors, wire cable, rusted parts, ignition systems, machine parts, door hinges, locks, nuts and bolts and refrigeration equipment. Areas of use include homes, hotels/motels, airplanes, cars and trucks, machine shops, oil rigs, manufacturing facilities, industrial plants and factories.

FEATURES & BENEFITS

- Versatile light duty formula penetrates, lubricates, prevents corrosion and displaces moisture
- Silicone free formula will not interfere with subsequent painting
- Non-flammable
- Meets MIL Spec C-2344

SPECIFICATIONS

FORM: Solvent Based Aerosol
ODOR: Chlorinated Solvent
COLOR: Clear
DETERGENCY: None
TOXICITY: 100 ppm OSHA PEL TWA
WETTING ABILITY: Saturates
STORAGE STABILITY: 1 Year +
COLD STABILITY: 0°F
PHOSPHATES: None

FLASH POINT: None
FLAME EXTENSION: None
SOLUBILITY IN WATER: 0%
SPECIFIC GRAVITY: 1.44
% VOLATILE BY VOLUME: 87%
pH: N/A
PROPELLANT: Carbon Dioxide
EVAPORATION RATE: Medium
BIODEGRADABILITY: No

LABEL INFORMATION

PIERCE PENETRATING LUBRICANT

PIERCE is a non-flammable powerful, multiple-action penetrant and protective shield. Can be used on either dry or wet surfaces. To ensure adequate protection, periodic checks should be made to determine the need for reapplication.

SUGGESTED USES


- Start Wet Engines
- Freeing Nuts & Bolts
- Laundromats
- Airplanes
- Electrical Panel Board
- Parking Meters
- Refrigeration Equipment
- Vending Machines
- Remove Moisture from Ignition Wires
- Stops Corrosion on Battery Terminals

DIRECTIONS: Spray liberally directly on area to be treated. Reapply periodically as required.

CAUTION: Vapor harmful. Contents under pressure. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F. Contains Petroleum Distillates. Contains Perchloroethylene. Keep out of reach of children. Harmful or fatal if swallowed. If swallowed, do not induce vomiting. Call physician immediately. If sprayed in eyes, flush with large amounts of water. Avoid excessive inhalation. Avoid prolonged or repeated contact with skin. Use only in well ventilated area.

CONTAINS (CAS#): Tetrachloroethylene (127-18-4), Petroleum Distillate (64741-44-2), Carbon Dioxide (124-38-9), Sorbitan Monooleate (1338-43-8), Methyl Salicylate (119-36-8).

HEALTH	2
FLAMMABILITY	1
REACTIVITY	0
PERSONAL	G



PACKAGING INFORMATION

12 – 16 oz cans per case, 16 oz net weight.