



# BODACIOUS

## HIGH PRESSURE, NON-MELT RED GREASE

### DESCRIPTION

**BODACIOUS** is a USDA authorized high temperature, non-melting, inorganic red grease which will withstand temperatures up to 500°F. It sprays out as a thick liquid which transforms into a grease in minutes. This product penetrates, lubricates and prevents rust on all metal parts. Containing a high pressure additive, it reduces wear and extends operating life of all parts and machinery. It prevents seizing and loosens frozen parts. It contains no fluorinated solvents making it more environmentally friendly than its traditional counterparts.

### APPLICATIONS

For use on machinery, conveyors, chains, cables, gears, winches, tools and rollers. Areas of use include farms, oil rigs and refineries, bottling plants, dairies, paper mills, cotton gins, air conditioning, industrial plants, textile plants, lumber mills, cement plants and automotive/motorcycle/marine repair.

### FEATURES & BENEFITS

- Prolongs life of metal parts
- High shock and impact resistance
- Contains corrosion and rust inhibitors
- Exceptional adhesive cohesive and anti-wear properties

### SPECIFICATIONS

**FORM:** Solvent Based Aerosol  
**ODOR:** Petroleum  
**COLOR:** Red  
**DETERGENCY:** None  
**TOXICITY:** 25 ppm OSHA TLV  
**WETTING ABILITY:** Saturates  
**STORAGE STABILITY:** 1 Year +  
**COLD STABILITY:** 0°F  
**PHOSPHATES:** None

**FLASH POINT:** >73°F TCC  
**FLAME EXTENSION:** 20"  
**SOLUBILITY IN WATER:** 0%  
**SPECIFIC GRAVITY:** 0.92  
**% VOLATILE BY VOLUME:** 48.5%  
**pH:** N/A  
**PROPELLANT:** Hydrocarbon  
**EVAPORATION RATE:** N/A  
**BIODEGRADABILITY:** No

### LABEL INFORMATION

#### BODACIOUS NON-MELT GREASE SPRAY

This product is a multi-purpose lubricant penetrant that seeks hard to reach areas for tough, long lasting grease protection. Product sprays out as a thick liquid which transforms into a grease in one to two minutes. Cured lubricant withstands heat to 500°F, moisture, acids, high pressure and is highly rust resistant. Use on chains, winches, conveyors, gears, cables, tools, hinges, bushings, pins, levers and rollers. A high pressure additive reduces wear and prolongs operational life of all machinery. Temperatures above 375°F may require periodic reapplication.


**DIRECTIONS FOR USE:** Shake well before using. Remove protective cap. Point opening in spray tip towards area to be sprayed. For hard to reach areas insert red extender tube in hole in tip. Apply a light coat by spraying in quick, short bursts. Work part to distribute product evenly over entire surface. Spray as necessary to insure full coverage.

**DANGER:** Flammable. Vapor harmful. Contents under pressure. Do not puncture or incinerate container. Do not use or store near heat or open flame. Exposure to temperatures above 120°F may cause bursting. Contains Tetrachloroethylene. Avoid breathing spray mist. Do not expose to eyes. If in eyes, flush thoroughly with water for 15 minutes. Use only in well ventilated areas. Avoid contact with skin.

**WARNING:** This product contains a chemical(s) known to the State of California to cause cancer.

**CONTAINS (CAS#):** Heptane (142-82-5), Heavy Naphthenic Petroleum Distillate (64742-52-5), Propane/n-Butane (68476-86-8), Tetrachloroethylene (127-18-4), Organophilic Clay (N/A).

HEALTH	2
FLAMMABILITY	2
REACTIVITY	0
PERSONAL	B



### PACKAGING INFORMATION

12 – 16 oz cans per case, 12 oz net weight