



# SLICK

## PTFE & MOLY PENETRATING LUBRICANT

### DESCRIPTION

**SLICK** is a USDA authorized penetrating lubricant containing PTFE. Frees frozen parts, penetrates, prevents rusting, lubricates. Quickly penetrates to free rusted parts. PTFE continues to lubricate after application. Contains a corrosion preventative to protect metal parts.

### APPLICATIONS

Used for loosening rusted parts and lubrication of wire cable, door hinges, chains, hoists, pulleys, cranes, fork lifts, sprockets, gears, blocks and tackle, conveyors, construction machinery, industrial parts and locks. Areas of use include farms, oil rigs and refineries, bottling plants, dairies, paper mills, cotton gins, air conditioning, industrial plants, textile plants, lumber mills, cement plants and automotive/motorcycle/marine repair.

### FEATURES & BENEFITS

- Contains PTFE and Moly for excellent lubrication
- Withstands heavy loads
- Resists rust and corrosion even in extreme conditions
- Prolongs life of machinery

### SPECIFICATIONS

**FORM:** Solvent Based Aerosol  
**ODOR:** Strong Solvent  
**COLOR:** Brown  
**DETERGENCY:** None  
**TOXICITY:** 400 ppm OSHA TLV  
**WETTING ABILITY:** Saturates  
**STORAGE STABILITY:** 1 Year +  
**COLD STABILITY:** 0°F  
**PHOSPHATES:** None

**FLASH POINT:** +110°F TCC  
**FLAME EXTENSION:** 18"  
**SOLUBILITY IN WATER:** 0%  
**SPECIFIC GRAVITY:** 0.83  
**% VOLATILE BY VOLUME:** 87%  
**pH:** N/A  
**PROPELLANT:** Hydrocarbon  
**EVAPORATION RATE:** Slow  
**BIODEGRADABILITY:** No

### LABEL INFORMATION

#### SLICK LUBRICANT PTFE PENETRATING LUBRICANT


Scientifically formulated penetrating oil and rust dissolver containing micron size particles of PTFE and Moly. This super penetrant carries the PTFE and molybdenum disulfide particles into the threads, crevices, etc. These particles act as millions of tiny ball bearings to prevent seizing and galling while the parts are being removed. This product is designed to be used on all dismantling jobs throughout the plant, shop or wherever parts are frozen or hard to operate. Quickly loosens corroded nuts, studs, bolts, flanges and pipe joints.

**DIRECTIONS:** Shake well. Remove protective cap and point spray opening in desired direction. Holding container 6-12 inches from surface to be treated, spray product liberally, saturating joints. Allow to set 5-10 minutes and break out. For extremely difficult jobs, saturate joints and allow to set 5-10 minutes, then tap lightly with a hammer and break out.

**DANGER: FLAMMABLE.** Contains Petroleum Distillates. Do not use near fire or open flame. Contents under pressure. Do not puncture. Do not store above 120°F. Do not throw container into fire or incinerator. Avoid frequent or prolonged contact with skin. Use only in well ventilated area. If swallowed, do not induce vomiting. Contact physician immediately.

**CONTAINS (CAS#):** Petroleum Distillate (64741-44-2), Isoparaffinic Hydrocarbon (64742-47-8), Propane/n-Butane (68476-86-8), Petroleum Distillate (64742-54-7), Ethyl Acetate (141-78-6).

HEALTH	1
FLAMMABILITY	2
REACTIVITY	0
PERSONAL	A



### PACKAGING INFORMATION

12 – 16 oz cans per case, 12 oz net weight