



EZ LUBE

FOOD GRADE WHITE GREASE

DESCRIPTION

EZ LUBE food grade white grease is a high purity complex white grease with superior heavy-duty metal to metal characteristics. Excellent for high load applications requiring a long grease life. Resists water and heat. Provides rust corrosion protection and superior lubrication to a wide variety of applications. Wide temperature range of -40°F to +550°F.

APPLICATIONS

For use on chains, winches, conveyors, gears, cables, hinges, pins, levers, rollers, ovens, dryers, threads, bearings, o-rings, linkages, pumps and valves. For use by bakeries, bottlers, breweries, canneries, dairies, egg processors, meat and poultry processors, pharmaceutical manufacturers and food processing and packaging plants.

FEATURES & BENEFITS

- Lubricates, Reducing Friction and Wear
- Resists Extreme Pressure, Corrosion & Water Washout
- White Coloration for Easy Visual Check
- High Viscosity, Clings to Vertical Surfaces
- Wide Temperature Range of -40° – 550°F
- Resists Throw-Off and Wash-Out, Excellent Adhesion Properties

SPECIFICATIONS

FORM: Solvent Based Aerosol
ODOR: Petroleum
COLOR: Creamy White
DETERGENCY: None
TOXICITY: 500 ppm OSHA TLV
WETTING ABILITY: None
STORAGE STABILITY: 1 year +
COLD STABILITY: 32°F
PHOSPHATES: None

FLASH POINT: N/A
FLAME EXTENSION: 18" +
SOLUBILITY IN WATER: None
SPECIFIC GRAVITY: 0.85
% VOLATILE BY VOLUME: 71%
pH: N/A
PROPELLANT: Hydrocarbon
EVAPORATION RATE: Slow
BIODEGRADABILITY: Yes

LABEL INFORMATION

EZ LUBE
FOOD GRADE WHITE GREASE

A multi-purpose, high purity food grade lubricant that provides long lasting grease protection. Cured lubricant withstands heat to 550°F. Temperatures above 400°F may require periodic reapplication.

FOR USE ON: Chains, Winches, Conveyors, Gears, Cables, Hinges, Pins, Levers, Rollers, Ovens, Dryers, Threads, Bearings, O-Rings, Linkages, Pumps and Valves.


FOR USE BY: Bakeries, Bottlers, Breweries, Canneries, Dairies, Egg Processors, Meat and Poultry Processors, Pharmaceutical Manufacturers and Food Processing and Packaging Plants.

DIRECTIONS: Shake well before using. Remove protective cap. Point opening in spray tip towards area to be sprayed. For hard to reach areas insert red extender tube in hole in tip. Apply a light coat by spraying in quick, short bursts. Work part to distribute product evenly over entire surface. Spray as necessary to insure full coverage.

DANGER: EXTREMELY FLAMMABLE. Do not use near sparks, heat or open flame. Use only in a well ventilated area. Contents under pressure. Keep out of reach of children. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F.

CONTAINS (CAS#): Propane/n-Butane (68476-86-8), Hexane (110-54-3), Mineral Oil (8042-47-5).

HEALTH	1
FLAMMABILITY	3
REACTIVITY	0
PERSONAL	B



Nonfood Compounds
H1
148101

PACKAGING INFORMATION

12 – 16 oz. cans per case, 10 oz. net weight