

OFF

CARBURETOR & CHOKE CLEANER



DANGER: POISON

DESCRIPTION

OFF is a USDA authorized product formulated for use on all types of carburetion and PCV systems in automobiles, buses, trucks and industrial equipment. Cleans and frees choke linkages, moving parts on carburetors and PCV valves. Removes grease, carbon deposits, oil, gumming and other materials. Fast drying. Leaves no film. Safe on oxygen sensors and catalytic converters.

APPLICATIONS

For use on automobiles, heat risers, buses, pcv valves and systems, carburetors, motorcycles, earth moving equipment. Cools automatic choke thermostat controls for faster adjustment time. Areas of use include automobile and motorcycle repair shops, bus maintenance facilities, factories and auto dealerships.

FEATURES & BENEFITS

- Improves vehicle efficiency
- Quickly cleans and frees sticking chokes
- Oxygen sensor and catalytic converter safe

SPECIFICATIONS

FORM: Solvent Based Aerosol
ODOR: Strong Solvent
COLOR: Clear
DETERGENCY: None
TOXICITY: 200 ppm OSHA PEL
WETTING ABILITY: Saturates
STORAGE STABILITY: 1 Year +
COLD STABILITY: 0°F
PHOSPHATES: None

FLASH POINT: 53°F TCC
FLAME EXTENSION: 24"
SOLUBILITY IN WATER: 78%
SPECIFIC GRAVITY: 0.81
% VOLATILE BY VOLUME: 78%
pH: N/A
PROPELLANT: Carbon Dioxide
EVAPORATION RATE: Fast
BIODEGRADABILITY: No

LABEL INFORMATION

OFF
CARBURETOR & CHOKE CLEANER

OFF carburetor and choke cleaner is the modern quick way to clean and lubricate automatic chokes, PCV valves and systems, heat risers and carburetors. Rapidly cleans carburetors without removing them from the car engine. Frees frozen or inoperative choke and carburetor linkages when frozen due to dirty parts. Cleans out PCV valves and hoses allowing system to operate properly. This product has been thoroughly tested to insure no adverse effects to oxygen sensor equipment.

DIRECTIONS:

CARBURETOR: Remove air filter. Liberally spray inside and outside of carburetor. Spray all linkages and manually operate until free moving.

CHOKE LINKAGE: Spray both sides of choke butterfly. Manually operate until free moving.


PCV SYSTEMS: When installing a new PCV Valve, remove hose from crankcase. While engine is running, spray carburetor cleaner into hose and allow carburetor to draw spray into hose and PCV Valve. If necessary, work valve manually until clean.

HEAT RISERS: A quick spray of carburetor cleaner will help free heat risers without leaving any residue.

DANGER: POISON. Extremely Flammable. Contents under pressure. Do not puncture or incinerate container. Do not use or store near heat or open flame. Exposure to temperatures above 120°F may cause bursting. Vapor harmful. May be fatal or cause blindness if swallowed. If swallowed, do not induce vomiting. Cannot be made non-poisonous. Consult physician.

CONTAINS (CAS #): Acetone (67-64-1), Methyl Alcohol (67-56-1), Xylene (1330-20-7), Isoparaffinic Hydrocarbon (64742-47-8), Carbon Dioxide (124-38-9).

HEALTH	2
FLAMMABILITY	3
REACTIVITY	1
PERSONAL	A



PACKAGING INFORMATION

12 – 16 oz cans per case, 13 oz net weight