

VROOM

STARTING FLUID

DESCRIPTION

VROOM is designed to aid gasoline and diesel engines with quick and easy starting power in cold, wet or freezing weather. Prevents excessive battery drain. Functions after use as a corrosion inhibitor and upper cylinder lubricant. Note: Do not use this product on glow plugs.

APPLICATIONS

For use on all automobile, truck, lawn mower, and upper cylinder lubricant, boat, chain saw, tractor, and other motors. Areas of use include machine shops, auto repair shops, truck stops, marinas, lawn mower repair shops and company fleet shops.

FEATURES & BENEFITS

- Provides quick, easy start-up in all weather conditions
- For use on all internal combustion, gasoline, and diesel engines
- Reduces battery drain

SPECIFICATIONS

FORM: Solvent Based Aerosol
ODOR: Ether
COLOR: Clear
DETERGENCY: N/A
TOXICITY: 400 ppm
WETTING ABILITY: N/A
STORAGE STABILITY: 1 Year
COLD STABILITY: -40°F
PHOSPHATES: None

FLASH POINT: <0°F TCC
FLAME EXTENSION: N/A
SOLUBILITY IN WATER: 0
SPECIFIC GRAVITY: 0.70
% VOLATILE BY VOLUME: 100%
pH: N/A
PROPELLANT: Carbon Dioxide
EVAPORATION RATE: None
BIODEGRADABILITY: No

LABEL INFORMATION

VROOM STARTING FLUID

VROOM aids gasoline and diesel engines in fast and easy start-up in all temperatures and weather conditions. Prolongs battery and starter life. Contains upper cylinder lubricants and anti-corrosive additives. Note: Do not use this product on glow plugs.

APPLICATIONS: For use on the following engines: automobiles, trucks, lawn mowers, boats, chainsaws, tractors, and other internal combustion engines. For use by automobile dealerships, auto repair shops, truck stops, equipment and auto rental outlets, marinas, lawn mower repair services, and company fleet divisions.


DIRECTIONS FOR USE Spray into air intake system (air cleaner, carburetor, or intake manifold) for 2 seconds prior to starting engine. Repeat if necessary. Do not flood engine. Avoid over-use.

DANGER: Extremely flammable. Harmful or fatal if swallowed or inhaled. May be harmful if absorbed through skin. Causes eye irritation. Contents under pressure. Avoid contact with eyes, skin and clothing. Do not take internally. Wash thoroughly after handling. Avoid breathing vapor. Use only with adequate ventilation. Keep away from heat, sparks and flame. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F. Keep out of direct sunlight. Prolonged or repeated overexposure may cause lung, nervous system, heart, gastrointestinal, and blood effects. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. **KEEP OUT OF REACH OF CHILDREN. SEE MATERIAL SAFETY DATA SHEET.**

FIRST AID: SKIN – Wash thoroughly with soap and water. EYES – Immediately flush with plenty of water. Call physician if irritation persists. INHALATION – Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention. INGESTION – If swallowed, do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Call physician or poison control center immediately.

CONTAINS (CAS#): Heptane (142-85-5), Diethyl Ether (60-29-7), Carbon Dioxide (124-38-9), Propane (74-98-6), Isobutane (75-28-5).

HEALTH	2
FLAMMABILITY	4
REACTIVITY	0
PERSONAL	G



PACKAGING INFORMATION

12 – 16 oz cans per case, 10.7 oz net weight